



EV9328-06

High Flow CSR Triple-MC² System

Delivers premium quality water for combination applications



High Flow CSR Triple-MC² System: EV9328-06

MC² Replacement Cartridge: EV9612-56

EC210 Prefilter Cartridge: EV9534-26

SR-X with SS-IMF Cartridge: EV9799-32

BENEFITS

One system provides premium quality water to high flow fountain dispensers, coffee makers and ice machines

New and improved Micro-Pure II media inhibits the growth of bacteria

Reduces chlorine taste and odor and other offensive contaminants that can adversely affect the taste of beverages

Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size and reduces health contaminants such as cysts

Increases the overall efficiency of equipment

20" prefilter captures larger dirt particles

SR-X with SS-IMF cartridge inhibits scale buildup in ice machines and coffee brewers

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

NSF Certified under NSF/ANSI Standards 42 and 53

INSTALLATION TIPS

Choose a mounting location suitable to support the full weight of the system when operating

Use 3/4" water line

Fountain equipment connections are made to the outlet part of the system before the SR-X system

Coffee brewer and ice machine connections are made after the SR-X feeder; a tee is required

Install vertically with cartridges hanging down. Allow 2-1/2" clearance below the cartridge for easy cartridge replacement

Flush cartridges by running water through flushing valve for five minutes at full flow

OPERATION TIPS

Change cartridges on a regular 6 month preventative maintenance program

Change cartridges when capacity is reached or when pressure falls below 10 psi

Change SS-IMF cartridge before Hydroblend™ compound is completely used up

Change prefilter cartridge when excessively dirty

Always flush the filter cartridge at time of installation and cartridge change

APPLICATION/SIZING

For multiple equipment and combination applications

Combination of coffee brewers, espresso machines, hot chocolate dispensers, fountain and ice machines

Rated Capacity: 27,000 gallons

SPECIFICATIONS

Overall Dimensions:

25.59"H x 30"W x 6.74"D

Inlet connection: 3/4"

Outlet connection: 3/4"

Service Flow Rate:

Maximum 5.0 gpm (18.9 Lpm)

Rated Capacity: 27,000 gallons

Pressure Requirements:

10 - 125 psi (0.7 - 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)


No electrical connection required

Shipping Weight: 39 lbs.

Operating Weight: 49 lbs.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

High Flow CSR Triple-MC² System



WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects
 Chemical Unit
 Taste and Odor Reduction
 Chlorine Reduction
 Mechanical Filtration Unit
 Particulate Reduction, Class I:
 99.9+ % reduction of particles
 one-half micron and larger in size
 Standard No. 53: Health Effects
 Mechanical Filtration Unit
 Turbidity Reduction
 Cyst Reduction
 Asbestos Reduction



Worldwide Headquarters:

EVERPURE, LLC
 1040 Muirfield Drive
 Hanover Park, Illinois 60133
 Toll Free (800) 323-7873
 Tel (630) 307-3000
 Fax (630) 307-3030
<http://www.everpure.com>

In Europe:

Pentair Water Belgium B.V./B.A.
 Industriepark Wolfstee
 Toekomstlaan 30
 B-2200 Herentals
 BELGIUM
 TEL: +32.(0).14.283.500
 FAX: +32.(0).14.283.505

In Japan:

Hashimoto MN Bldg. 7F
 3-25-1 Hashimoto Sagamihara-Shi
 Kanagawa 229-1103
 JAPAN
 TEL: 81.(0)42.775.3011
 FAX: 81.(0)42.775.3015